

PROBLEM TO BE SOLVED: To provide a receiver, in which the risk for sending a large quantity of busy data or audio data to a data communication network such as the Internet is reduced. SOLUTION: Concerning a terminal adapter un der communication connection with a call originating side via the Internet, when incoming request data expressing an incoming request are received from a call-originating side (S102), audio packets expressing ring back tones are succ essively transmitted to a call-originating side (S105). At this time, the number of packets to be transmitted is limited on the basis of the number of packets received from the call- originating side.

```
COPYRIGHT: (C)2001,JPO
국가
            JP (Japan)
공개번호
            2001-345803 (2001.12.14)
                현재진행상태 보기
                   JP 문서보기
문헌종류
            A (Unexamined Publication)
                  문헌정보보기
출원번호
            2000-168206 (2000.06.05)
발명자
            OTA MASATAKA
            FUJIKAWA KENJI
            NAKANISHI YASUAKI
츑원인
            WORLD AXLE KK
            OI ELECTRIC CO LTD
국제특하분류(I H04L-012/02, H04L-012/56, H04M-003/00, H04M-011/00
PC))
FI
            H04M-003/00 B; H04M-011/00 302; H04L-011/02 Z; H04L-011/20 102 A
F-Term
            5K030: GA13 GA15 HA08 HB01 HC01 JA03 JT01
            5K051: CC02 DD13 HH27 JJ13
            5K101: LL02 SS06 SS08 UU15
테마코드
            5K030; 5K051; 5K101
WIPS 패밀리
                 패밀리정보 보기
```